

# Shotcrete Pump



## FEATURES

- Heavy-Duty Design
- High Pressure and Production Rate
- Perfect for Shotcrete and Slabs
- Pumps 3/8" Pea Rock and 3/4" Material
- Optional Air Vibrator
- Remix Agitator (standard on model 636)

**SHOTCRETE  
SLAB POURS  
PEA-ROCK  
CONCRETE REPAIR  
RETAINING WALLS  
GROUTING**

## TECHNICAL SPECIFICATIONS

	Model 536	Model 636
<b>Max. Output</b>	36 cu yd/hr (28 m <sup>3</sup> /hr)	50 cu yd/hr (38 m <sup>3</sup> /hr)
<b>Pressure</b>	900 psi (62 bar)	800 psi (55 bar)
<b>Max Aggregate Size</b>	3/4" minus (25 mm)	3/4" minus (25 mm)
<b>Concrete Cylinder Diameter</b>	5" (127 mm)	6" (152 mm)
<b>Concrete Cylinder Stroke</b>	36" (914 mm)	36" (914 mm)
<b>Full Flow S-Tube</b>	5" (127 mm)	6" (152 mm)
<b>Discharge Outlet Size</b>	5" (127 mm)	5" (127 mm)
<b>Power Source</b>	Diesel 60 hp	Diesel 80 hp
<b>Length</b>	162"	162"
<b>Width</b>	70"	70"
<b>Weight</b>	4,000 lb (1,814 kg)	4,300 lb (1,950 kg)
<b>Tires</b>	15"	15"
<b>Axle</b>	Single	Single

Maximum output and pressure cannot be reached simultaneously. Performance will vary depending on power unit, hydraulic pressure, cycle rate, mix design and placement line.